

[illegible]

1206 N. Palafox Street
Pensacola, Florida 32501
Phone: (850) 994-9503

CA Lic. No. 29588
www.mckimcreed.com

CIVIL
GENERAL NOTES

PROJ. START DATE:	09/27/2021
MCE PROJ. #	07617-0011
DRAWN	CPH
DESIGNED	CPH
CHECKED	ALM
PROJ. MGR.	DPJ


HORIZONTAL
AS NOTED

VERTICAL:
N/A

DRAWING NUMBER

A
REVISION

BID SET NOT FOR CONSTRUCTION



EAST SIDE OF PARKING LOT LOOKING WEST



WEST SIDE OF PARKING LOT LOOKING EAST



ENTRANCE TO PARKING LOT


[illegible]

**2021 PAVING REHAB - CENTRAL, JAY,
MILTON HS**

CIVIL

JAY HIGH SCHOOL - EXISTING CONDITIONS

PROJ. START DATE: 09/27/2021		SCALE		C300	
MCE PROJ. # 07617-0011		HORIZONTAL:		DRAWING NUMBER	
DRAWN CPH		AS NOTED		A	
DESIGNED CPH		VERTICAL:		REVISION	
CHECKED ALM		N/A			
PROJ. MGR. DPJ					



EAST SIDE OF PARKING LOT LOOKING WEST



WEST SIDE OF PARKING LOT LOOKING EAST



ENTRANCE TO PARKING LOT

[illegible]

2021 PAVING REHAB - CENTRAL, JAY, MILTON HS



CIVIL

JAY HIGH SCHOOL - DEMOLITION PLAN

PROJ. START DATE:	09/27/2021
MCE PROJ. #	07617-0011
DRAWN	CPH
DESIGNED	CPH
CHECKED	ALM
PROJ. MGR.	DPJ

SCALE HORIZONTAL: AS NOTED VERTICAL: N/A	C301 DRAWING NUMBER A REVISION
---	--

STATUS: **PHASE 3**
BID SET NOT FOR CONSTRUCTION



ABANDONED CONCRETE BASE AND BASKETBALL HOOP SECTION, TO BE REMOVED



EXISTING BASKETBALL HOOPS AND UTILITIES, TO BE PROTECTED IN PLACE



ALL SIDEWALK, CURB, AND FENCING TO BE PROTECTED IN PLACE

REV. NO.	DESCRIPTION	DATE
REVISIONS		



MCKIM & CREED
1206 N. Palafox Street
Pensacola, Florida 32501
Phone: (850) 994-9503

CA Lic. No. 29588
www.mckimcreed.com

2021 PAVING REHAB - CENTRAL, JAY, MILTON HS

CIVIL


MILTON HIGH SCHOOL - DEMOLITION PLAN

PROJ. START DATE: 09/27/2021
MCE PROJ. # 07817-0011
DRAWN: EBB
DESIGNED: CBR
CHECKED: ADM
PROJ. MGR: DVB

STATUS: **BID SET NOT FOR CONSTRUCTION**

SCALE
HORIZONTAL: AS NOTED
VERTICAL: N/A


C401
DRAWING NUMBER
A
REVISION




TRACK LAYOUT DETAIL

NOT TO SCALE

1
C500



ASPHALT TRACK PAVING SECTION 2
NOT TO SCALE C500



IN AREAS WHERE GRADES OUTSIDE OF NEW TRACK ARE HIGHER THAN TRACK SURFACE, RIBBON CURB SLOPE MUST BE REVERSED SUCH THAT WATER FROM UPGRADE AREAS CAN MORE EASILY FLOW ACROSS TRACK SURFACE.

CONCRETE RIBBON CURB 3
NOT TO SCALE C500

NOTES:

1. TRACK LAYOUT MUST BE STRIPED TO ACCOMMODATE THE FOLLOWING EVENTS: 100m, 200m, 400m, 800m, 1 MILE, AND 2 MILE RUNS; BOYS 110m HURDLES; GIRLS 100m HURDLES; 4x100m RELAY; 4x400m RELAY; 4x800m RELAY.
2. TRACK LAYOUT MUST BE IN INSTALLED AND IN ACCORDANCE WITH FLORIDA HIGH SCHOOL SPORTS ASSOCIATION AND NATIONAL FEDERATION OF HIGH SCHOOL ASSOCIATIONS REQUIREMENTS. STRIPING LAYOUT MUST BE COMPLETED BY A QUALIFIED SPECIALISTS, SUCH AS A CERTIFIED TRACK BUILDER OR AN EXPERIENCED TRACK STRIPER. THE SPECIALIST MUST HAVE A COMPLETE KNOWLEDGE OF BASIC TRACK GEOMETRY, AS WELL AS A THOROUGH UNDERSTANDING OF THE RULES OF THE SPECIFIC GOVERNING BODY OR BODIES UNDER WHICH COMPETITION WILL BE CONDUCTED. THIS BODY OF KNOWLEDGE MUST INCLUDE PRESCRIBED PATHS OF RUNNERS, BREAK-LINE COMPENSATION REQUIREMENTS AND NUMBER OF LAPS RUN IN LANES FOR ANY GIVEN RACE. BEFORE ANY CALCULATIONS ARE MADE, THE SPECIALIST MUST MEET WITH THE OWNER'S DESIGNATED REPRESENTATIVE TO DISCUSS OPTIONS AND UNIQUE REQUIREMENTS SUCH AS COLOR CODE, DESIGN OF THE MARKINGS AND ANY SPECIAL EVENTS TO BE MARKED.
3. CONTRACTOR MUST COMPLETE AND FURNISH TO ENGINEER PRIOR TO REQUEST SUBSTANTIAL COMPLETION A CLASS 4 MARKINGS CERTIFICATION FOR RUNNING TRACKS, AS PROVIDED IN THE AMERICAN SPORTS BUILDERS ASSOCIATION PUBLICATION, "RUNNING TRACKS, A CONSTRUCTION & MAINTENANCE MANUAL, NINTH EDITION, 2016."

[illegible]

McKIM & CREED

1206 N. Palafox Street
Pensacola, Florida 32501
Phone: (850) 994-9503


CA Lic. No. 29588
www.mckimcreed.com

2021 PAVING REHAB - CENTRAL, JAY, MILTON HS

DETAILS


TRACK DETAILS

PROJ. START DATE: 09/27/2021 MCE PROJ. # 07611-0011 DRAWN CPH DESIGNED CPH CHECKED ALM PROJ. MGR. DPJJ	SCALE HORIZONTAL: AS NOTED VERTICAL: N/A	C500 DRAWING NUMBER A REVISION
---	---	---



- NOTES:**
1. CONSTRUCTION ENTRANCES PROVIDE AN AREA WHERE MUD CAN BE REMOVED FROM VEHICLE TIRES BEFORE THEY LEAVE THE CONSTRUCTION SITE. THE MOTION OF THE VEHICLE AS IT MOVES OVER THE GRAVEL CONSTRUCTION MATERIAL DISLODGES CAKED MUD.
 2. IF THE ACTION OF THE VEHICLE ON THE GRAVEL PAD IS NOT SUFFICIENT TO DISLODGE MUD, THEN THE TIRES MUST BE WASHED BEFORE THE VEHICLE LEAVES THE SITE.
 3. UTILIZE GRAVEL, 2"—3" (MIN.) IN DIAMETER. GRAVEL LAYER SHOULD BE AT LEAST 6" THICK. THE PAD SHOULD BE AT LEAST 50' LONG. WIDTH SHOULD BE APPROPRIATE TO VEHICLE SIZE.

ROCK CONSTRUCTION ACCESS 4
NOT TO SCALE C501




ADA PARKING STALL 5
NOT TO SCALE C501



ADA WHEELCHAIR MARKING

NOT TO SCALE

9
C501



ADA PARKING SIGNAGE

NOT TO SCALE

6
C501




SILTATION FENCE 7
NOT TO SCALE C501



- NOTES:
1. SEE WRITTEN SPECIFICATIONS FOR FULL DETAILS.
 2. PLACE SOD BEGINNING AT THE TOE OF THE SLOPE AND LONG EDGE PERPENDICULAR TO DIRECTION OF FLOW.
 3. SOD SHALL BE PINNED ON ALL SLOPES 4:1 OR STEEPER, IN AREAS OF CONCENTRATED DRAINAGE FLOWS, AND ANYWHERE THAT THERE IS DANGER OF SOD SLIPPING.
 4. INSTALL SOD EDGES FLUSH WITH FINISHED GRADE OR ADJOINING SOD.

SODDING DETAIL 11
NOT TO SCALE C501




BALES SHALL BE PLACED IN A SINGLE ROW, LENGTHWISE ON THE CONTOUR, WITH ENDS OF ADJACENT BALES TIGHTLY ABUTTING EACH OTHER. ALL BALES SHALL BE EITHER WIRE-BOUND OR STRING-TIED. THE BARRIER SHALL BE ENTRENCHED AND BACKFILLED. THE FIRST STAKE IN EACH BALE SHALL BE DRIVEN TOWARD THE PREVIOUSLY LAID BALE TO FORCE THE BALES TOGETHER. THE GAPS BETWEEN BALES SHALL BE CHINKED (FILLED BY WEDGING) WITH STRAW.

HAYBALE INSTALLATION

NOT TO SCALE

8

C501

[illegible]

2021 PAVING REHAB - CENTRAL, JAY, MILTON HS

DETAILS

SITE DETAILS

PROJ. START DATE:	09/27/2021
MCE PROJ. #	07617-0011
DRAWN	CPH
DESIGNED	CPH
CHECKED	ALM
PROJ. MGR.	DPJ

STATUS:

SCALE
HORIZONTAL:
S NOTED
VERTICAL:
N/A

C501

A

PHASE 3

US: **PHASE 3**
BID SET NOT FOR CONSTRUCTION